

# Slurry Tankers



## Slurry Tankers

## KEY DETAILS



**Hydraulic Brakes**

**6" filler and discharge points**

**3" sight glass**

**A blanked off side fill point**

**15ft of 6" suction hose**

**Half inch/2" washdown  
adaptor plug**

**6" quick attach suction hose  
filler**

**8000 ltr pump on 1150 to 1650  
gallon tanks**

**10,000 ltr pump on 2000 to  
3000 gallon tanks**

**Sprung drawbar standard on  
2000 to 3000 gallon tankers**

## Capacities

<b>GALLON</b>	1150	1350	1650	2000	2350	2700
<b>LITRE</b>	5200	6100	7500	9000	10650	12250

### 1150g – 1650g Standard With:

- 8 Stud 9 Tonne Axle
- Solid Drawbar
- 550/60 x 22.5 Wheels

### 2000g - 2700g Standard With:

- 10 Stud Commercial 14 Tonne Axle
- Sprung Drawbar
- 2000g – 23.1 x 26 Wheels
- 2350g – 28.1 x 26 Wheels
- 2700g – 30.5 x 32 Wheels

<b>Additional Optional Extras</b>	
Sprung Drawbar 1150g – 1650g	Galvanised Tank
Sludgigator Top Cannon	Hyd. Inside Mixer
Auto Fill Arm	Trailing Shoe (6m + 7.5m)
Hose Reel (Road Use Tanker)	Slurry Agitator Pump



**Slurry Agitator Pump**



**Trailing Shoe**